

Upright Fire Sprinkler Standard Response K5.6 1/2"

UL Listed Upright Fire Sprinklers, Standard Response, 5mm Glass Bulb, K5.6, 1/2" Connecting Thread. Model: KS803

Standard Coverage, Standard Response, 5mm Glass Bulb, K5.6, 1/2" Connecting Thread.

UL Listed KSFCO Standard Coverage Upright Sprinklers are glass-bulb types designed for use in various commercial applications. The temperature range of 5mm and 3mm glass bulb is from: 135°F/57°C, 155°F /68°C, 175°F/79°C, 200°F/93°C up to 286°F/141°C.

Bulb Nominal Dia. & Response	Ø5mm Standard Response
Thread Size	NPT1/2" or BSPT1/2"
Nominal Orifice Size	1/2 Inch
Nominal K-Factor	5.6 (U.S.)/80 (metric)
Max. Working Pressure	175psig/1.2MPa (12bar)
Sprinkler Finish	Natural Brass, Chrome Finished or White Painting (RAL9010)
Nominal Temp. Rating °F (°C)	135°F/(57°C) 155°F/(68°C) 175°F/(79°C) 200°F/(93°C) 286°F/(141°C)
Listing and Approvals	UL Listed

Upright Fire Sprinkler Quick Response K5.6 1/2"

UL Listed Upright Fire Sprinklers, Quick Response, 3mm Glass Bulb, K5.6, 1/2" Connecting Thread. Model: KS804

Standard Coverage, Quick Response, 3mm Glass Bulb, K5.6, 1/2" Connecting Thread.

UL Listed KSFCO Standard Coverage Upright Sprinklers are glass-bulb types designed for use in various commercial applications. The temperature range of 5mm and 3mm glass bulb is from: 135°F/57°C, 155°F /68°C, 175°F/79°C, 200°F/93°C up to 286°F/141°C.

Bulb Nominal Dia. & Response	Ø3mm Quick Response
Thread Size	NPT1/2" or BSPT1/2"
Nominal Orifice Size	1/2 Inch
Nominal K-Factor	5.6 (U.S.)/80 (metric)
Max. Working Pressure	175psig/1.2MPa (12bar)
Sprinkler Finish	Natural Brass, Chrome Finished or White Painting (RAL9010)
Nominal Temp. Rating °F (°C)	135°F/(57°C) 155°F/(68°C) 175°F/(79°C) 200°F/(93°C) 286°F/(141°C)
Listing and Approvals	UL Listed



**UPRIGHT
STANDARD
SPRINKLERS**



**UPRIGHT
QUICK RESPONSE
SPRINKLERS**



www.shieldfirefighting.com



Location : North Al Batinah governorate, Sohar FZ ,Oman

Contact US: 0096871714938